

SAFETY DATA SHEET

1. Identification

Product identifier Food Grade Silicone

Other means of identification

Product Code No. 03040 (Item# 1003296)

Recommended use Silicone-based multi-purpose lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas
Skin corrosion/irritation Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements

Health hazards



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very

toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves. Avoid release to the environment.

Material name: Food Grade Silicone sps us

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell. Collect spillage.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,1-difluoroethane	HFC-152a	75-37-6	30 - 40
naphtha (petroleum), hydrotreated light		64742-49-0	20 - 30
n-heptane		142-82-5	10 - 20
3-methylhexane		589-34-4	5 - 10
methylcyclohexane		108-87-2	5 - 10
2-methylhexane		591-76-4	3 - 5
2,3-dimethylpentane		565-59-3	1 - 3
3-ethylpentane		617-78-7	1 - 3
3,3-dimethylpentane		562-49-2	< 0.3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire

and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

Material name: Food Grade Silicone

SDS US

No. 03040 (Item# 1003296) Version #: 05 Revision date: 10-18-2018 Issue date: 02-03-2014

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m3	
		500 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Values	;		
Components	Туре	Value	
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm	
	TWA	400 ppm	
2-methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	

Material name: Food Grade Silicone

Components	t Values Type	Value	
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm	
	TWA	400 ppm	
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm	
	TWA	400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	
methylcyclohexane (CAS 108-87-2)	TWA	1600 mg/m3	
		400 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3	
		100 ppm	
n-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
US. Workplace Environment Components	ntal Exposure Level (WEEL) Guides Type	Value	
1,1-difluoroethane (CAS	TWA	2700 mg/m3	
75-37-6)		1000 ppm	
logical limit values	No biological exposure limits noted for the ingredient(s).		
propriate engineering	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product. Eye wash fountain and emergency showers are recommended.		
trols	exposure limits have not been establis wash facilities and emergency shower	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was	
	exposure limits have not been establis wash facilities and emergency shower	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was recommended.	
	exposure limits have not been establis wash facilities and emergency shower fountain and emergency showers are	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was recommended.	
vidual protection measures	exposure limits have not been establis wash facilities and emergency shower fountain and emergency showers are , such as personal protective equipment	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was recommended. ent (or goggles).	
vidual protection measures Eye/face protection Skin protection	exposure limits have not been establis wash facilities and emergency shower fountain and emergency showers are , such as personal protective equipmed Wear safety glasses with side shields	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was recommended. ent (or goggles). e. Viton/butyl.	
vidual protection measures Eye/face protection Skin protection Hand protection	exposure limits have not been establis wash facilities and emergency shower fountain and emergency showers are such as personal protective equipmed. Wear safety glasses with side shields. Wear protective gloves such as: Nitrile Wear appropriate chemical resistant of the facilities of the engineering controls are not feasible NIOSH-approved cartridge respirators.	shed, maintain airborne levels to an acceptable level. Eye r should be available when handling this product. Eye was recommended. ent (or goggles). e. Viton/butyl. clothing. e or if exposure exceeds the applicable exposure limits, u with an organic vapor cartridge. Use a self-contained es and for emergencies. Air monitoring is needed to	

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

Material name: Food Grade Silicone

General hygiene

considerations

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol. Color Water-white. Odor Mild petroleum. **Odor threshold** Not available. Not available. pН

-195.9 °F (-126.6 °C) estimated Melting point/freezing point

Initial boiling point and boiling range

149 °F (65 °C) estimated

Flash point

< 23 °F (< -5 °C) Tag Closed Cup

Evaporation rate Fast.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower 1.1 % estimated

(%)

Flammability limit - upper

7 % estimated

(%)

Vapor pressure 2931.4 hPa estimated

> 1 (air = 1)Vapor density Relative density 0.78 estimated

Solubility(ies)

Negligible. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 509 °F (265 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available. Percent volatile 95.3 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with Conditions to avoid

incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Material name: Food Grade Silicone No. 03040 (Item# 1003296) Version #: 05 Revision date: 10-18-2018 Issue date: 02-03-2014 Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

1,1-difluoroethane (CAS 75-37-6)

Acute Inhalation

LC50 Rat 383000 ppm, 2 hours

3-methylhexane (CAS 589-34-4)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 20 mg/l, 4 hours

Oral

LD50 Rat > 2000 mg/kg

methylcyclohexane (CAS 108-87-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 4000 mg/kg

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat 61 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

n-heptane (CAS 142-82-5)

<u>Acute</u>

Dermal

LD50 Rabbit 3000 mg/kg

Inhalation

Vapor

LC50 Rat > 73.5 mg/l, 4 hours

Oral

LD50 Rat 25000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Material name: Food Grade Silicone

No. 03040 (Item# 1003296) Version #: 05 Revision date: 10-18-2018 Issue date: 02-03-2014

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,1-difluoroethane0.75methylcyclohexane3.61n-heptane4.66

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light 10 - 25000

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance

with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes, but exempt from the regulations.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

ERG Code 10L

Material name: Food Grade Silicone

SDS US

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.


Environmental hazards

Marine pollutant Yes, but exempt from the regulations.

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-difluoroethane (CAS 75-37-6)

Safe Drinking Water Act

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Not regulated.

Gas under pressure categories Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

1,1-difluoroethane (CAS 75-37-6)

2,3-dimethylpentane (CAS 565-59-3)

3-methylhexane (CAS 589-34-4)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

US. Massachusetts RTK - Substance List

1.1-difluoroethane (CAS 75-37-6)

2,3-dimethylpentane (CAS 565-59-3)

2-methylhexane (CAS 591-76-4)

3-methylhexane (CAS 589-34-4)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

2,3-dimethylpentane (CAS 565-59-3)

2-methylhexane (CAS 591-76-4)

3,3-dimethylpentane (CAS 562-49-2)

3-methylhexane (CAS 589-34-4)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

US. Rhode Island RTK

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 60 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

Material name: Food Grade Silicone

SDS US

No. 03040 (Item# 1003296) Version #: 05 Revision date: 10-18-2018 Issue date: 02-03-2014

State

This product is regulated as a Silicone Based Multi-Purpose Lubricant. This product is compliant Consumer products

for use in all 50 states.

VOC content (CA) 60 % 60 % VOC content (OTC)

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Chemical Substances (AICS) Canada Domestic Substances List (DSL) No Canada Non-Domestic Substances List (NDSL) Yes China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe No

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Yes Japan Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

Issue date 02-03-2014 10-18-2018 **Revision date** Prepared by Allison Yoon

Version # 05

Further information CRC # 1750887

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Food Grade Silicone

SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).