



Bright Zinc-It® Instant Cold Galvanize, 13 Wt Oz
 No. 18414 | Item# 1005244 | Case# 1005243

Product Description	An acrylic based, sacrificial zinc coating that protects ferrous metals from oxidizing. Creates a barrier film between the environment & the base metal to prevent the formation or spread of rust & corrosion. Meets requirements of ASTM-A780.
Color	Silver
Applications	On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Cold Galvanized Coating
Net Fill	13 Wt Oz
UPC Code	078254184142
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.68H x 5.62W x 11.31D in
Cases Per Pallet	150
Case Weight	13 lbs
I 2 of 5 Code	30078254184143
Appearance	Gray Liquid
Flash point (F)	-2.2°F
Flash point (C)	-19°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	No
Evaporation Rate	Fast
Dry Time - Fully Dry	48 Hours
Dry Time - Tack Free	20 Minutes

Last revised: 1/8/2020
 Page 1 of 2





Recoat	20 Minutes to 16 Hours
Coverage	28 to 32 Sq Ft per aerosol
Working Temp (F)	Not Determined
Working Temp (C)	Not Determined
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Not Determined
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	45.9
VOC g/L (Consumer Product def)	579
VOC lbs/gal (Consumer Prod def)	4.83
VOC Category	Aerosol Coating: Metallic
MIR Limit (EPA)	1.9
MIR Limit (CA)	1.25
MIR Value	1.1
Removal (How To)	Remove with petroleum solvents.